

---

# **gqlmod Documentation**

*Release 0.8.2.dev1*

**Jamie Bliss**

**Mar 23, 2020**



## CONTENTS:

<b>1</b>	<b>Using gqlmod</b>	<b>3</b>
1.1	Summary . . . . .	3
1.2	Example . . . . .	3
1.3	Writing Query Files . . . . .	4
1.4	Query functions . . . . .	4
1.5	Using different provider contexts . . . . .	4
1.6	Major Providers . . . . .	4
1.7	API Reference . . . . .	5
<b>2</b>	<b>Tool Usage</b>	<b>7</b>
2.1	gqlmod command . . . . .	7
2.2	GitHub Action . . . . .	7
<b>3</b>	<b>Writing a Provider</b>	<b>9</b>
3.1	Provider Classes . . . . .	9
3.2	Entry point . . . . .	10
3.3	Helpers . . . . .	10
3.4	Extensions . . . . .	11
<b>4</b>	<b>Indices and tables</b>	<b>13</b>
	<b>Python Module Index</b>	<b>15</b>
	<b>Index</b>	<b>17</b>



gqlmod allows you to import GraphQL Query (.gql) files as modules and call the queries and mutations defined there. It will validate your queries at import time, to surface any problems as soon as possible.

gqlmod also defines mechanisms for handling different services (called providers) and different contexts with those services.



## USING GQLMOD

### 1.1 Summary

1. Install the `gqlmod` PyPI package, as well as any providers you need
2. Call `gqlmod.enable_gql_import()` as soon as possible (maybe in your `__main__.py` or top-level `__init__.py`)
3. Import your query file and start calling your queries.

### 1.2 Example

Listing 1: queries.gql

```
#~starwars~
query HeroForEpisode($ep: Episode!) {
  hero(episode: $ep) {
    name
    ... on Droid {
      primaryFunction
    }
    ... on Human {
      homePlanet
    }
  }
}
```

Listing 2: app.py

```
import gqlmod
gqlmod.enable_gql_import()

from queries import HeroForEpisode

resp = HeroForEpisode(ep='JEDI')
assert not resp.errors

print(resp.data)
```

## 1.3 Writing Query Files

Query files are simply text files full of named GraphQL queries and mutations.

One addition is the provider declaration:

```
#~starwars~
```

This tells the system what provider to connect to these queries, and therefore how to actually query the service, what schema to validate against, etc.

The name of the provider should be in the provider's docs.

## 1.4 Query functions

The generated functions have a specific form.

Query functions only take keyword arguments, matching the variables defined in the query. Optional arguments with defaults may naturally be omitted.

The function returns a `graphql.ExecutionResult`. It has the following attributes:

- `data`: The result data
- `errors`: A list of errors that occurred, or an empty list if none occurred

Note that whether query functions are synchronous or asynchronous is up to the provider; see its documentation.

## 1.5 Using different provider contexts

All installed providers are available at startup, initialized with no arguments. For most services, this will allow you to execute queries as an anonymous user. However, most applications will want to authenticate to the service. You can use `gqlmod.with_provider()` to provide this data to the provider.

`gqlmod.with_provider()` is a context manager, and may be nested. That is, you can globally authenticate as your app, but also in specific parts authenticate as a user.

The specific arguments will vary by provider, but usually have this basic form:

```
with gqlmod.with_provider('spam-service', token=config['TOKEN']):  
    resp = spam_queries.GetMenu(amount_of_spam=None)
```

## 1.6 Major Providers

Here is a list of some maintained providers:

- `starwars`: Builtin! A demo provider that works on static constant data.
- `cirrus-ci`: From `gqlmod-cirrusci`, connects to [Cirrus CI](#)
- `github`: From `gqlmod-github`, connects to the [GitHub v4 API](#)

You may be able to discover a provider at these places:

- [The `gqlmod` topic on GitHub](#)



- [Searching gqlmod on PyPI](#)

## 1.7 API Reference

`gqlmod.with_provider` (*name*, *\*\*params*)

Uses a new instance of the provider (with the given parameters) for the duration of the context.

`gqlmod.enable_gql_import` ()

Enables importing `.gql` files.



## TOOL USAGE

In addition the module, several tools are available.

### 2.1 gqlmod command

Included in the package is a `gqlmod` tool. This provides static analysis functionality outside of your software.

#### 2.1.1 `gqlmod check`

Checks graphql files for syntax and schema validity. Unlike importing, all findable errors are reported.

Give the list of files to check, or pass `-search` to scan the current directory (recursively).

### 2.2 GitHub Action

The check function is also available as a GitHub Action (with extra annotation integration).

Listing 1: `.github/workflows/gqlmod.yml`

```
name: gqlmod check

on: push

jobs:
  check:
    runs-on: ubuntu-latest
    steps:
      - uses: actions/checkout@v1
        with:
          fetch-depth: 1
      - uses: gqlmod/check-action@master
        with:
          GITHUB_TOKEN: ${ secrets.GITHUB_TOKEN }
```

You do need to use the `actions/checkout` action before calling `gqlmod/check-action`, and the `GITHUB_TOKEN` argument is required.



## WRITING A PROVIDER

Writing a provider is fairly straightforward.

1. Define a provider class
2. Add an entry point declaration

### 3.1 Provider Classes

A provider class is only required to be callable with a specific signature.

```
import graphql

class MyProvider:
    def __init__(self, token=None):
        self.token = token

    def __call__(self, query, variables):
        # Do stuff here

        return graphql.ExecutionResult(
            errors=[],
            data={'spam': 'eggs'}
        )
```

The arguments it takes are:

- `query`: (string) The query to give to the server
- `variables`: (dict) The variables for that query

The provider should return a `graphql.ExecutionResult` as shown above.

## 3.2 Entry point

In order to be discoverable by `gqlmod`, providers must define entrypoints. Specifically, in the `graphql_providers` group under the name you want `.gql` files to use. This can take a few different forms, depending on your project. A few examples:

Listing 1: `setup.cfg`

```
[options.entry_points]
graphql_providers =
    starwars = gqlmod_starwars:StarWarsProvider
```

Listing 2: `setup.py`

```
setup(
    # ...
    entry_points={
        'graphql_providers': [
            'starwars = gqlmod_starwars:StarWarsProvider'
        ]
    },
    # ...
)
```

Listing 3: `pyproject.toml`

```
# This is for poetry-based projects
[tool.poetry.plugins.graphql_providers]
"starwars" = "gqlmod_starwars:StarWarsProvider"
```

## 3.3 Helpers

In order to help with common cases, `gqlmod` ships with several helpers

Note that many of them have additional requirements, which are encapsulated in extras.

### 3.3.1 `urllib`

Helpers for using `urllib` to build a provider. You probably want `UrllibJsonProvider`.

Requires the no extras.

```
class gqlmod.helpers.urllib.UrllibJsonProvider
    A UrllibProvider that uses a JSON-based POST
```

```
class gqlmod.helpers.urllib.UrllibProvider
    Help build an HTTP-based provider based on requests.
```

You should fill in `endpoint` and possibly override `modify_request()`.

```
endpoint: str = None
    The URL to send requests to
```

```
modify_request (req, variables)
    Apply policies about the request, primarily authentication.
```

Accepts a `urllib.request.Request` object.

### 3.3.2 aiohttp

Helpers for using `aiohttp` to build a provider.

Requires the `aiohttp` extra.

**class** `gqlmod.helpers.aiohttp.AiohttpProvider`

Help build an HTTP-based provider based on `aiohttp`.

You should fill in `endpoint` and possibly override `modify_request_args()`.

**endpoint:** `str = None`

The URL to send requests to.

**modify\_request\_args** (*variables, kwargs*)

Apply policies about the request, primarily authentication.

**timeout:** `aiohttp.client.ClientTimeout = None`

Timeout policy to use, if any.

**use\_json:** `bool = False`

Whether a JSON-based or form-like request should be used.

## 3.4 Extensions

In addition to the core querying interface, providers may influence the import process in a few different ways. These are all implemented as optional methods on the provider instance.

### 3.4.1 get\_schema\_str()

Providers may override the standard schema discovery mechanism by implementing `get_schema_str()`. This is useful for providers that don't have a primary service or don't allow anonymous access at all.

This method must be synchronous. An async variation is not supported.

**Default behavior:** Issue a GraphQL introspection query via the standard query path.

**Parameters:** None.

**Returns:** A `str` of the schema, in standard GraphQL schema language.

### 3.4.2 codegen\_extra\_kwargs()

Providers may add keyword arguments (variables) to the query call inside the generated module. These will be passed through the query pipeline back to the provider.

**Default behavior:** No additional variables are inserted.

**Parameters:**

- `graphql_ast` (positional, `graphql.language.OperationDefinitionNode`): The AST of the GraphQL query in question
- `schema` (positional, `graphql.type.GraphQLSchema`): The schema of the service

**Returns:** A `dict` of the names mapping to either simple values or `ast.AST` instances. (Note that the returned AST will be embedded into a right-hand expression context.)



## INDICES AND TABLES

- genindex
- modindex



## PYTHON MODULE INDEX

### g

`gqlmod`, 5

`gqlmod.helpers.aiohttp`, 11

`gqlmod.helpers.urllib`, 10



## A

AiohttpProvider (class in *gqlmod.helpers.aiohttp*),  
11

## E

enable\_gql\_import() (in module *gqlmod*), 5  
endpoint (*gqlmod.helpers.aiohttp.AiohttpProvider* at-  
tribute), 11  
endpoint (*gqlmod.helpers.urllib.UrlLibProvider*  
attribute), 10

## G

*gqlmod* (module), 5  
*gqlmod.helpers.aiohttp* (module), 11  
*gqlmod.helpers.urllib* (module), 10

## M

modify\_request() (*gqlmod.helpers.urllib.UrlLibProvider*  
method), 10  
modify\_request\_args()  
(*gqlmod.helpers.aiohttp.AiohttpProvider*  
method), 11

## T

timeout (*gqlmod.helpers.aiohttp.AiohttpProvider* at-  
tribute), 11

## U

UrllibJsonProvider (class in  
*gqlmod.helpers.urllib*), 10  
UrllibProvider (class in *gqlmod.helpers.urllib*), 10  
use\_json (*gqlmod.helpers.aiohttp.AiohttpProvider* at-  
tribute), 11

## W

with\_provider() (in module *gqlmod*), 5